



No. Z2 066213 0113 Rev. 00

Veetorni 9, Jüri alevik, Rae vald
75301 Harjumaa
ESTONIA



tuv-sud.com/ps-cert

Playground equipment

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 713131318-14

Valid until: 2023-09-02

Date, 2018-12-12

(Jens Biesenack)



Product Service

CERTIFICATE

No. Z2 066213 0113 Rev. 00

Model(s):

LM001, LM002, LM003, LM005, LM006, LM006-1, LM006-2, LM007 PE, LM009, LM010, LM016, LM017, LM018, LM100, LM102, LM103, LM105, LM202, LM202-1, LM202-3, LM203, LM204, LM205, LM208, LM208-1, LM208-2, LM209, LM210, LM211, LM212, LM213, LM213-1, LM213-2, LM214-2, LM215, LM215-1, LM217, LM217-1, LM218, LM219, LM220, LM220-1, LM221, LM222, LM222-1, LM223, LM225, LM225-1, LM226, LM226-1, LM227, LM228, LM229, LM231, LM310, LMK004

Combination playing construction with slides, ramps, stairs, climbing nets, climbing walls, platforms, bridges and fireman's pole.

Posts 98x98mm: laminated wood, aluminium (AL) or galvanized steel.

Platforms, stairs: laminated wood or with hotspray lamination (MF).

Panels: plywood/ PE plastic (PE).

Walls, roofs, plates, seats, tables: plywood/ PE plastic.

Fireman's pole: galvanized steel

Pole anchor: galvanized steel

Model	length	width	height
LM001	2,15m	0,95m	4,11m
LM002	2,65m	0,95m	3,44m
LM003	2,16m	2,55m	3,40m
LM005	1,90m	2,62m	4,99m
LM006	2,65m	2,63m	4,23m
LM006-1	2,16m	2,61m	3,14m
LM006-2	2,66m	1,78m	7,06m
LM007 PE	2,20m	0,72m	3,42m
LM009	3,66m	3,04m	4,65m
LM010	3,66m	2,32m	4,50m
LM016	3,87m	4,79m	5,47m
LM017	3,89m	3,78m	7,24m
LM018	3,31m	4,32m	6,72m
LM100	3,82m	3,82m	4,95m
LM102	3,82m	4,95m	5,15m
LM103	2,85m	3,36m	4,49m
LM105	3,45m	2,99m	7,96m
LM202	2,90m	3,29m	3,74m



Product Service

CERTIFICATE

No. Z2 066213 0113 Rev. 00

LM202-1	2,90m	1,78m	5,82m
LM202-3	3,37m	2,86m	4,59m
LM203	2,97m	4,79m	5,21m
LM204	2,97m	4,59m	5,47m
LM205	2,97m	4,59m	5,47m
LM208	2,85m	4,32m	7,75m
LM208-1	2,85m	4,32m	6,38m
LM208-2	2,85m	5,48m	6,38m
LM209	3,01m	2,87m	5,71m
LM210	2,90m	3,74m	5,38m
LM211	2,85m	4,51m	4,57m
LM212	3,82m	4,73m	4,83m
LM213	3,82m	3,49m	4,73m
LM213-1	3,81m	4,73m	6,71m
LM213-2	3,80m	6,36m	6,71m
LM214-2	2,51m	3,92m	4,80m
LM215	2,90m	3,62m	8,64m
LM215-1	2,91m	2,89m	5,04m
LM217	3,76m	4,22m	4,50m
LM217-1	3,76m	3,34m	4,50m
LM218	3,66m	3,09m	4,50m
LM219	3,82m	3,65m	4,44m
LM220	3,74m	3,99m	7,22m
LM220-1	4,34m	4,35m	8,67m
LM221	3,27m	4,33m	5,84m
LM222	3,82m	5,25m	5,45m
LM222-1	3,40m	4,69m	4,80m
LM223	2,37m	5,12m	6,42m
LM225	3,00m	3,83m	8,96m
LM225-1	3,45m	4,42m	5,90m
LM226	3,93m	3,88m	7,52m
LM226-1	3,95m	5,18m	7,55m
LM227	3,66m	3,10m	7,51m
LM228	3,45m	4,53m	6,25m
LM229	2,60m	7,48m	5,85m
LM231			
LM310	3,93m	7,46m	8,19m



Product Service

CERTIFICATE

No. Z2 066213 0113 Rev. 00

LMK004	1,71m	4,15m	4,40m
--------	-------	-------	-------

Tested

EN 1176-1:2017

according to:

EN 1176-3:2017

Production

066213

Facility(ies):